

PROCESSES FOR PRODUCING HOLLOW MOLDED ARTICLES

FIELD OF THE INVENTION

5 The present invention relates to a process and an apparatus for producing a hollow molded article by a blow molding process. More specifically, the present invention directs to a process and an apparatus for production of hollow molded articles such as resin ducts and hoses as a final product by cutting unnecessary portions of an
10 intermediate molded article, particularly, by cutting an end of the intermediate molded article in a mold intermittently or successively in a blow-molding step.

BACKGROUND OF THE INVENTION

15 A cylindrical hollow article such as resin tube, hose and duct is conventionally produced by blow-molding a molten resin parison in a mold. The blow-molding processes comprise a step for setting a resin parison excluded from a die in a cavity formed by a pair of metal
20 mold-members, a step for closing molding members, and a step for blowing a pressurized air into the resin parison to expand and form a hollow product. The molding of such hollow articles produces unnecessary portions or sites at the ends of the final product. Thus, the unnecessary
25 portion in the final product is usually formed at the closed or narrow end of the final product.

Therefore, after taking out the intermediate

09073295-050501

hollow product from the metal mold, the unnecessary portion of the intermediate hollow product is cut manually by using a cutting means such as knife to produce a cylindrical hollow product. However, this cutting operation increases
5 a production cost, and forms an irregular end surface on the cutting face, since the manual cutting operation is conducted individually outside the metal mold of the blow-molding apparatus. Thus, the finishing process for the cut irregular face is required, and the productivity
10 of the hollow articles would be reduced.

SUMMARY OF THE INVENTION

It is, therefore, an object of the present invention to provide a process and an apparatus for
15 producing a hollow product or article by cutting efficiently an unnecessary portion(s) of an intermediate hollow product in a molding process without cutting operations after blow-molding.

It is another object of the present invention to
20 provide a process and an apparatus for producing a hollow product or article with improving productivity and reducing production cost.

The inventor of the present invention did intensive investigation to achieve the above objects, and found that
25 use of a cutting means movable forwardly and backwardly in a metal mold relative to an intermediate product improves the cutting efficiency of unnecessary portions of the

09872295-065001

intermediate product to produce high quality hollow products stably. The present invention is based on the above finding.

Thus, a process for producing a hollow molded
5 article having an open end by blow-molding method, which
comprises a setting step for setting or putting a resin
parison in cavity formed by a pair of metal mold members,
a blowing step for blowing a pressurized gas (a compressed
10 gas) into the resin parison to form an intermediate molded
article, and a cutting step for cutting a predetermined
part or section (i.e. cutting site) from the intermediate
molded article with forward or backward movement of a
cutting means which is movable crossly the cavity. In the
process, the predetermined part or portion of the
15 intermediate molded article is cut with a cutting means
which is attached movably to the one member of the metal
mold members. The cutting means may be movable
reciprocally in a cross direction relative to the
longitudinal or axial direction of the cavity or the metal
20 mold members. The cutting means may be guided movably
along a groove or slit formed in the metal mold members,
and the predetermined part (or cutting site) of the
intermediate molded article is cut with the cutting means.
The cutting means may comprise a blade being crossable
25 (traversable) in an across direction relative to the
longitudinal or axial direction of the intermediate molded
article to be cut, and at least one end of the intermediate

09873295 " 060501

09873295"060501
T05090"5627860

molded article is cut by the blade of the cutting means.
The invention further discloses a process for cutting an
unnecessary portion(s) of a hollow molded article in a metal
mold. This process may comprise setting a resin parison
5 in cavity formed by a pair of metal mold members, blowing
a pressurized gas into the resin parison for expansion or
inflation to form an intermediate molded article, and
cutting a predetermined part or portion of the intermediate
molded article with forward movement of a blade of a cutting
10 means which is movable crossly the cavity.

A blow-molding apparatus of the invention is used
for producing a hollow molded article. The apparatus may
comprise a pair of metal mold members which are openable
or closable each other and are formable a cavity for
15 accommodating a resin parison, a blowing means for blowing
a pressurized gas into the resin parison to form an
intermediate molded article, a cutting means, which is
movable crossly the cavity, for cutting a predetermined
part (i.e. cutting site) of the intermediate molded article,
20 and a reciprocating means for reciprocating the cutting
means.

The inner wall of the metal mold members may have
a groove or slit extending to a cross direction relative
to the axial direction of the intermediate molded article,
25 and the cutting means may comprise a cutter unit for cutting
the intermediate molded article and an actuating means (e.g.
cylindrical actuating means) for actuating the cutter unit

forward or backward direction along the groove or slit. The groove or slit may be formed at a position of the inner wall corresponding to an end or edge of a final molded article. Further, the cutter unit has a various blade such as a circular hollow blade being acceptable the setting or accommodation of the resin parison, at least an inclined or curved blade which contacts pointedly or linearly substantially with the surface of the intermediate molded article, and so on. The blow-molding apparatus may further comprise a stopper being displaceable forward or backward against (or along axial direction of) an end of the resin parison and closable tightly the end of the resin parison in association with the mold members, and a control unit for controlling the forward or backward movement of the cutting means in response to the backward or forward movement of the stopper relative to the intermediate molded article. In the operations by the control unit, the forward displacement of the stopper regulates the advancement of the cutting means and the backward displacement of the stopper allows to move the cutting means forward.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic sectional side view showing one embodiment of a metal mold in a cutting step of the present invention,

Figure 2 is a schematic sectional view taken along

line II of Figure 1,

Figure 3 is a partially fragmentary sectional view of the metal mold showing an end portion of an intermediate molded article,

5 Figure 4 is a schematic sectional side view showing another embodiment of a metal mold in a cutting step of the present invention,

Figure 5 is a schematic plane view showing end portion of the metal mold,

10 Figure 6 is a schematic sectional view taken along line VI of Figure 4, and

Figure 7 is a partially fragmentary sectional view of the metal mold showing an end portion of an intermediate molded article.

15

DETAILED DESCRIPTION OF THE INVENTION

With reference to Figures, the preferred embodiments of the present invention will be illustrated. Figs. 1-3 show one embodiment of the present invention. 20 Fig. 1 shows a schematic sectional side view of a metal mold in the cutting step of the present invention, Fig. 2 shows a schematic sectional view taken along line II of Fig. 1, and Fig. 3 is a partially fragmentary sectional view of the metal mold showing an end portion of an 25 intermediate molded article.

A metal mold comprises a pair of metal mold members 1 and 2 (i.e. an upper metal mold member 1 and a lower metal

09873295-060501
T05090"5627860

09873295"060501

mold member 2) which may be closely contacted with each other to form a parting line 3. The metal mold members 1 and 2 are separable or openable and closable each other, and form a cavity 4 for accommodating a molten resin parison by closing operation. The pair of the metal mold members 1 and 2 closes tightly the both ends of the resin parison. After closing the metal mold members 1 and 2, a pressurized gas is blown or introduced into the resin parison to expand the resin parison for forming an intermediate hollow molded article or product 5 having a shape corresponding to the configuration of the cavity 4.

A cutting tool 10 as a cutting means having a cutter unit 12 is attached or secured to one metal mold member 2 (i.e. the lower metal mold member) of the members with a bolt 11, and the cutter unit 12 is movable reciprocally in an across direction (particularly, perpendicular direction) relative to an axial or longitudinal direction of the cavity 4 or the hollow molded product 5. In more detail, on or at a predetermined inner site (e.g. inner wall site) of the metal mold members 1 and 2 corresponding to a cutting site 8 where an unnecessary portion(s) of the intermediate molded product is cut, a groove 7 or slit is formed as a space for disposing slidably the cutter unit 12. The groove 7 or slit extends to a cross direction relative to the axial direction of the intermediate molded article 5, and the cutter unit 12 is disposed movably in the groove 7 or slit. Further, the movement or

displacement of the cutter unit 12 is controlled by an oil hydraulic cylinder 14 as a reciprocating means or an actuating means. Thus, the cutter unit 14 is movable crossly the cavity and the forward or backward movement along the groove 7 or slit can be conducted by actuating the cylinder 14 as the reciprocating means for reciprocating the cutting means.

The cutter unit 12 has a plate-like configuration and is scooped out at an area to form a circular inner blade 13 having a keen-edged inner blade. The circular inner blade 13 is somewhat projected inwardly into the cavity 4 from the inner surface of the mold members 1 and 2 for forming the intermediate molded product 5 having the cutting site 8. Thus, the axis of the circular inner blade 13 is coincided substantially with the axis of the cavity 4 or molded product 5, and the inner diameter of the circular inner blade 13 is somewhat smaller than that of the cavity 4. Thus, the blade is arranged so as to cross the longitudinal or axial direction of the intermediate molded article to be cut.

According to the apparatus, a blow-molded hollow article having an open end can be produced by cutting the intermediate molded article in the blow-molding process. Firstly, a molten resin parison excluded from a die by an extruder (not shown) is set or arranged on the metal mold member 2. In this operation, an end portion of the parison corresponding to the unnecessary portion 6 of the

060501 060505 060509 060513 060517 060521 060525 060529 060533 060537 060541 060545 060549 060553 060557 060561 060565 060569 060573 060577 060581 060585 060589 060593 060597 060601 060605 060609 060613 060617 060621 060625 060629 060633 060637 060641 060645 060649 060653 060657 060661 060665 060669 060673 060677 060681 060685 060689 060693 060697 060701 060705 060709 060713 060717 060721 060725 060729 060733 060737 060741 060745 060749 060753 060757 060761 060765 060769 060773 060777 060781 060785 060789 060793 060797 060801 060805 060809 060813 060817 060821 060825 060829 060833 060837 060841 060845 060849 060853 060857 060861 060865 060869 060873 060877 060881 060885 060889 060893 060897 060901 060905 060909 060913 060917 060921 060925 060929 060933 060937 060941 060945 060949 060953 060957 060961 060965 060969 060973 060977 060981 060985 060989 060993 060997 061001 061005 061009 061013 061017 061021 061025 061029 061033 061037 061041 061045 061049 061053 061057 061061 061065 061069 061073 061077 061081 061085 061089 061093 061097 061101 061105 061109 061113 061117 061121 061125 061129 061133 061137 061141 061145 061149 061153 061157 061161 061165 061169 061173 061177 061181 061185 061189 061193 061197 061201 061205 061209 061213 061217 061221 061225 061229 061233 061237 061241 061245 061249 061253 061257 061261 061265 061269 061273 061277 061281 061285 061289 061293 061297 061301 061305 061309 061313 061317 061321 061325 061329 061333 061337 061341 061345 061349 061353 061357 061361 061365 061369 061373 061377 061381 061385 061389 061393 061397 061401 061405 061409 061413 061417 061421 061425 061429 061433 061437 061441 061445 061449 061453 061457 061461 061465 061469 061473 061477 061481 061485 061489 061493 061497 061501 061505 061509 061513 061517 061521 061525 061529 061533 061537 061541 061545 061549 061553 061557 061561 061565 061569 061573 061577 061581 061585 061589 061593 061597 061601 061605 061609 061613 061617 061621 061625 061629 061633 061637 061641 061645 061649 061653 061657 061661 061665 061669 061673 061677 061681 061685 061689 061693 061697 061701 061705 061709 061713 061717 061721 061725 061729 061733 061737 061741 061745 061749 061753 061757 061761 061765 061769 061773 061777 061781 061785 061789 061793 061797 061801 061805 061809 061813 061817 061821 061825 061829 061833 061837 061841 061845 061849 061853 061857 061861 061865 061869 061873 061877 061881 061885 061889 061893 061897 061901 061905 061909 061913 061917 061921 061925 061929 061933 061937 061941 061945 061949 061953 061957 061961 061965 061969 061973 061977 061981 061985 061989 061993 061997 062001 062005 062009 062013 062017 062021 062025 062029 062033 062037 062041 062045 062049 062053 062057 062061 062065 062069 062073 062077 062081 062085 062089 062093 062097 062101 062105 062109 062113 062117 062121 062125 062129 062133 062137 062141 062145 062149 062153 062157 062161 062165 062169 062173 062177 062181 062185 062189 062193 062197 062201 062205 062209 062213 062217 062221 062225 062229 062233 062237 062241 062245 062249 062253 062257 062261 062265 062269 062273 062277 062281 062285 062289 062293 062297 062301 062305 062309 062313 062317 062321 062325 062329 062333 062337 062341 062345 062349 062353 062357 062361 062365 062369 062373 062377 062381 062385 062389 062393 062397 062401 062405 062409 062413 062417 062421 062425 062429 062433 062437 062441 062445 062449 062453 062457 062461 062465 062469 062473 062477 062481 062485 062489 062493 062497 062501 062505 062509 062513 062517 062521 062525 062529 062533 062537 062541 062545 062549 062553 062557 062561 062565 062569 062573 062577 062581 062585 062589 062593 062597 062601 062605 062609 062613 062617 062621 062625 062629 062633 062637 062641 062645 062649 062653 062657 062661 062665 062669 062673 062677 062681 062685 062689 062693 062697 062701 062705 062709 062713 062717 062721 062725 062729 062733 062737 062741 062745 062749 062753 062757 062761 062765 062769 062773 062777 062781 062785 062789 062793 062797 062801 062805 062809 062813 062817 062821 062825 062829 062833 062837 062841 062845 062849 062853 062857 062861 062865 062869 062873 062877 062881 062885 062889 062893 062897 062901 062905 062909 062913 062917 062921 062925 062929 062933 062937 062941 062945 062949 062953 062957 062961 062965 062969 062973 062977 062981 062985 062989 062993 062997 063001 063005 063009 063013 063017 063021 063025 063029 063033 063037 063041 063045 063049 063053 063057 063061 063065 063069 063073 063077 063081 063085 063089 063093 063097 063101 063105 063109 063113 063117 063121 063125 063129 063133 063137 063141 063145 063149 063153 063157 063161 063165 063169 063173 063177 063181 063185 063189 063193 063197 063201 063205 063209 063213 063217 063221 063225 063229 063233 063237 063241 063245 063249 063253 063257 063261 063265 063269 063273 063277 063281 063285 063289 063293 063297 063301 063305 063309 063313 063317 063321 063325 063329 063333 063337 063341 063345 063349 063353 063357 063361 063365 063369 063373 063377 063381 063385 063389 063393 063397 063401 063405 063409 063413 063417 063421 063425 063429 063433 063437 063441 063445 063449 063453 063457 063461 063465 063469 063473 063477 063481 063485 063489 063493 063497 063501 063505 063509 063513 063517 063521 063525 063529 063533 063537 063541 063545 063549 063553 063557 063561 063565 063569 063573 063577 063581 063585 063589 063593 063597 063601 063605 063609 063613 063617 063621 063625 063629 063633 063637 063641 063645 063649 063653 063657 063661 063665 063669 063673 063677 063681 063685 063689 063693 063697 063701 063705 063709 063713 063717 063721 063725 063729 063733 063737 063741 063745 063749 063753 063757 063761 063765 063769 063773 063777 063781 063785 063789 063793 063797 063801 063805 063809 063813 063817 063821 063825 063829 063833 063837 063841 063845 063849 063853 063857 063861 063865 063869 063873 063877 063881 063885 063889 063893 063897 063901 063905 063909 063913 063917 063921 063925 063929 063933 063937 063941 063945 063949 063953 063957 063961 063965 063969 063973 063977 063981 063985 063989 063993 063997 064001 064005 064009 064013 064017 064021 064025 064029 064033 064037 064041 064045 064049 064053 064057 064061 064065 064069 064073 064077 064081 064085 064089 064093 064097 064101 064105 064109 064113 064117 064121 064125 064129 064133 064137 064141 064145 064149 064153 064157 064161 064165 064169 064173 064177 064181 064185 064189 064193 064197 064201 064205 064209 064213 064217 064221 064225 064229 064233 064237 064241 064245 064249 064253 064257 064261 064265 064269 064273 064277 064281 064285 064289 064293 064297 064301 064305 064309 064313 064317 064321 064325 064329 064333 064337 064341 064345 064349 064353 064357 064361 064365 064369 064373 064377 064381 064385 064389 064393 064397 064401 064405 064409 064413 064417 064421 064425 064429 064433 064437 064441 064445 064449 064453 064457 064461 064465 064469 064473 064477 064481 064485 064489 064493 064497 064501 064505 064509 064513 064517 064521 064525 064529 064533 064537 064541 064545 064549 064553 064557 064561 064565 064569 064573 064577 064581 064585 064589 064593 064597 064601 064605 064609 064613 064617 064621 064625 064629 064633 064637 064641 064645 064649 064653 064657 064661 064665 064669 064673 064677 064681 064685 064689 064693 064697 064701 064705 064709 064713 064717 064721 064725 064729 064733 064737 064741 064745 064749 064753 064757 064761 064765 064769 064773 064777 064781 064785 064789 064793 064797 064801 064805 064809 064813 064817 064821 064825 064829 064833 064837 064841 064845 064849 064853 064857 064861 064865 064869 064873 064877 064881 064885 064889 064893 064897 064901 064905 064909 064913 064917 064921 064925 064929 064933 064937 064941 064945 064949 064953 064957 064961 064965 064969 064973 064977 064981 064985 064989 064993 064997 065001 065005 065009 065013 065017 065021 065025 065029 065033 065037 065041 065045 065049 065053 065057 065061 065065 065069 065073 065077 065081 065085 065089 065093 065097 065101 065105 065109 065113 065117 065121 065125 065129 065133 065137 065141 065145 065149 065153 065157 065161 065165 065169 065173 065177 065181 065185 065189 065193 065197 065201 065205 065209 065213 065217 065221 065225 065229 065233 065237 065241 065245 065249 065253 065257 065261 065265 065269 065273 065277 065281 065285 065289 065293 065297 065301 065305 065309 065313 065317 065321 065325 065329 065333 065337 065341 065345 065349 065353 065357 065361 065365 065369 065373 065377 065381 065385 065389 065393 065397 065401 065405 065409 065413 065417 065421 065425 065429 065433 065437 065441 065445 065449 065453 065457 065461 065465 065469 065473 065477 065481 065485 065489 065493 065497 065501 065505 065509 065513 065517 065521 065525 065529 065533 065537 065541 065545 065549 065553 065557 065561 065565 065569 065573 065577 065581 065585 065589 065593 065597 065601 065605 065609 065613 065617 065621 065625 065629 065633 065637 065641 065645 065649 065653 065657 065661 065665 065669 065673 065677 065681 065685 065689 065693 065697 065701 065705 065709 065713 065717 065721 065725 065729 065733 065737 065741 065745 065749 065753 065757 065761 065765 065769 065773 065777 065781 065785 065789 065793 065797 065801 065805 065809 065813 065817 065821 065825 065829 065833 065837 065841 065845 065849 065853 065857 065861 065865 065869 065873 065877 065881 065885 065889 065893 065897 065901 065905 065909 065913 065917 065921 065925 065929 065933 065937 065941 065945 065949 065953 065957 065961 065965 065969 065973 065977 065981 065985 065989 065993 065997 066001 066005 066009 066013 066017 066021 066025 066029 066033 066037 066041 066045 066049 066053 066057 066061 066065 066069 066073 066077 066081 066085 066089 066093 066097 066101 066105 066109 066113 066117 066121 066125 066129 066133 066137 066141 066145 066149 066153 066157 066161 066165 066169 066173 066177 066181 066185 066189 066193 066197 066201 066205 066209 066213 066217 066221 066225 066229 066233 066237 066241 066245 066249 066253 066257 066261 066265 066269 066273 066277 066281 066285 066289 066293 066297 066301 066305 066309 066313 066317 066321 066325 066329 066333 066337 066341 066345 066349 066353 066357 066361 066365 066369 066373 066377 066381 066385 066389 066393 066397 066401 066405 066409 066413 066417 066421 066425 066429 066433 066437 066441 066445 066449 066453 066457 066461 066465 066469 066473 066477 066481 066485 066489 066493 066497 066501 066505 066509 066513 066517 066521 066525 066529 066533 066537 066541 066545 066549 066553 066557 066561 066565 066569 066573 066577 066581 066585 066589 066593 066597 066601 066605 066609 066613 066617 066621 066625 066629 066633 066637 066641 066645 066649 066653 066657 066661 066665 066669 066673 066677 066681 066685 066689 066693 066697 066701 066705 066709 066713 066717 066721 066725 066729 066733 066737 066741 066745 066749 066753 066757 066761 066765 066769 066773 066777 066781 066785 066789 066793 066797 066801 066805 066809 066813 066817 066821 066825 066829 066833 066837 066841 066845 066849 066853 066857 066861 066865 066869 066873 066877 066881 066885 066889 066893 066897 066901 066905 066909 066913 066917 066921 066925 066929 066933 066937 066941 066945 066949 066953 066957 066961 066965 066969 066973 066977 066981 066985 066989 066993 066997 067001 067005 067009 067013 067017 067021 067025 067029 067033 067037 067041 067045 067049 067053 067057 067061 067065 067069 067073 067077 067081 067085 067089 067093 067097 067101 067105 067109 067113 067117 067121 067125 067129 067133 067137 067141 067145 067149 067153 067157 067161 067165 067169 067173 067177 067181 067185 067189 067193 067197 067201 067205 067209 067213 067217 067221 067225 067229 067233 067237 067241 067245 067249 067253 067257 067261 067265 067269 067273 067277 067281 067285 067289 067293 067297

intermediate molded article 5 is inserted in or disposed on the inner arc blade 13 of the cutter unit 12 which is connected to the metal mold member 2.

After setting the resin parison having a given length in the space formed in the inner side of the metal mold member 2, the metal mold member 2 is closed by the other metal mold member 1 tightly to accommodate and hold the resin parison into the cavity 4 of the metal mold members 1 and 2, a pressurized (compressed) air is blown into the resin parison by a blowing means such as an air nozzle (not shown) to expand and press the resin parison against the inner surface of the metal mold. Thus, the intermediate molded article 5 having an outer configuration corresponding to the cavity 4 can be formed.

With molding the intermediate molded article 5, the circular inner blade 13 of the cutter unit 12 encroaches into the wall of the intermediate molded article 5 at the cutting site 8. After blow-molding, the intermediate molded article 5 may be cooled and preferably the introduced pressurized air may be exhausted from the parison. In the cutting step, the cutter unit 12 is actuated and advanced forward by the oil hydraulic cylinder 14 in the cross direction relative to the cavity 4 to reach a position shown by a two-dot chain line in Fig. 1. The advancement or forward movement of the blade 13 efficiently and accurately cuts the wall of the intermediate molded article 5 at predetermined part or portion (i.e. the cutting site 8)

09373295 "060501

with focusing the cutting force to the cutting site 8, since the blade 13 has been encroached or entered into the wall of the intermediate molded article 5. Thus, the unnecessary portion 6 (e.g. end or edge) in the final product can be cut and separated from the final hollow product with ease by a simple manner.

Following the cutting step, the metal mold member 1 is separated from the metal mold member 2 to take out the final hollow product wherein the unnecessary portion was cut. In such process, since the blow-molding step and the cutting step can be conducted successively or intermittently, any conventional post-processing step for the product having an open end such as a resin duct can be omitted.

Now reference to Figs. 4-7, another embodiment of the invention will be described in detail. Fig. 4 is a schematic sectional side view showing another embodiment of a metal mold in a cutting step of the present invention, Fig. 5 is a schematic plane view showing end portion of the metal mold, Fig. 6 is a schematic sectional view taken along line VI of Figure 4, and Fig. 7 is a partially fragmentary sectional view of the metal mold showing an end portion of an intermediate molded article.

As same as in Figs 1-3, a separable metal mold comprises a pair of metal mold members 1 and 2 (i.e. an upper metal mold member 1 and a lower metal mold member 2) which may be closely contacted with each other to form

09873295-050501
T05090"5627860

09873295 "060501
T05090 52E 7860

a parting line 3. The metal mold members 1 and 2 accommodate a molten resin parison and form a cavity 4 for molding an intermediate molded hollow article or product 5 by blowing a pressurized gas and expanding the resin parison. In this embodiment, one end of the longitudinal linear cavity 4 formed by the metal mold members 1 and 2 is not closed even if closing operation of the metal mold members, and a stopper 20, which is displaceable forward or backward along axial direction of the end of the linear cavity by an oil hydraulic cylinder 21, is disposed at the end side of the metal mold members 1 and 2. That is, the stopper 20 is closable of one end of the resin parison disposed in the longitudinal linear cavity 4 in association or cooperation of a pair of the metal mold members 1 and 2 to form an unnecessary portion 6 of the intermediate molded article 5. The pair of the metal mold members 1 and 2 closes tightly the other end of the resin parison and defines the outer side surface of the intermediate molded article 5. Thus, the movement or displacement of the stopper 20 is controlled by connecting the stopper 20 to the oil hydraulic cylinder 21 attached to one metal mold member 2 (i.e. the lower metal mold member).

Further, as same as in the embodiment mentioned above, a cutting tool 10 as a cutting means having a cutter unit 12 is attached movably to one metal mold member 2 (i.e. the lower metal mold member) with a bolt 11, and the cutter unit 12 is movable in an across direction (particularly,

perpendicular direction) relative to an axial direction of the cavity 4 or the hollow molded product 5. In more detail, at a predetermined site of the inner surface (e.g. inner wall) of the metal mold members 1 and 2 corresponding to a cutting site 8 where an unnecessary portion(s) of the intermediate molded product is cut, a groove 7 or slit is formed as a space for slidably disposing the cutter unit 12. The cutter unit 12 is disposed movably in the groove 7 or slit and the movement or displacement of the cutter unit 12 is controlled by an actuation of an oil hydraulic cylinder 14. Thus, the cutter unit 12 is movable forward or backward along the groove 7 or slit by actuating the cylinder 14.

The cutter unit 12 is formed in a plate-like configuration having a triangular keen-edged blade 13 at one end. The blade 13 at an original position is in the groove (or slit) 7 which is isolated or interrupted from the cavity 4 by the stopper 20. To be specific, the forward displacement of the stopper 20 closes the end of the resin parison and regulates or inhibits the advancement of the blade 13 of the cutting means at the original position, and the backward displacement of the stopper 20 allows to move the blade 13 of the cutting means forward to an advanced position for cutting the end of the intermediate molded product 5. These operations can be controlled by a controlling means. Thus, the apparatus further provides with a control unit for controlling the forward or backward

09873295 "060501

movement of the cutting means in response to the backward or forward movement of the stopper 20 relative to the intermediate molded article.

According to the above apparatus, the end or edge
5 (unnecessary portion) of the intermediate molded article can be efficiently cut in the metal mold by the blow-molding process. Thus, a molten resin parison excluded from a die by an extruder (not shown) is set or arranged along the inner concave of the metal mold member 2. After setting
10 the resin parison having a given length on the metal mold member (the lower metal mold member) 2, the metal mold member (the upper metal mold member) 1 is closed tightly with the other metal mold member 2, and the stopper 20 is actuated forward against (or along axial direction of) the
15 end of the parison to close the end of the cavity 4 or the end of the resin parison. With the forward movement of the stopper 20, the tip or edge of the stopper 20 is passed through the groove (or slit) 7 to contact with the edge of the metal mold members 1 and 2, and the closed space
20 "cavity 4" is formed by the metal mold members 1 and 2 and the stopper 20 to accommodate and hold the resin parison in the cavity 4. A pressurized air is blown into the resin parison by an air nozzle (not shown) to expand and press the resin parison against the inner surface of the metal
25 mold. Thus, the intermediate molded article 5 having an outer configuration corresponding to the cavity 4 can be formed.

09873295-060501
T060990-5227880

After blow-molding, the intermediate molded article 5 is cooled and preferably the introduced pressurized air is exhausted from the parison. In the cutting step, a control unit controls the forward or backward movement of the cutting means in response to the backward or forward movement of the stopper relative to the intermediate molded article. The stopper 20 is moved backward by actuating the oil hydraulic cylinder 21 to open the groove 7 which is communicable with the cavity 4 through the wall thickness of the intermediate molded article 5. In response to the backward movement of the stopper 20, the cutter unit 12 is actuated and advanced forward by the oil hydraulic cylinder 14 in the cross direction relative to the axis direction of the cavity 4 to reach a position shown by a two-dot chain line in Fig. 4. The advancement of the cutter unit 12 causes encroachment of the blade 13 into the wall, and further advancement of the blade 13 cuts efficiently and accurately the wall thickness of the intermediate molded article 5 at the cutting site 8 with concentrating the cutting force to the cutting site 8. Thus, the unnecessary portion 6 in the final product can be cut and separated from the final hollow product with ease by a simple manner.

Following the cutting step, the metal mold members 1 and 2 are separated or opened each other to take out the final hollow product. These steps or operations can be conducted repeatedly or intermittently by use of the

09873295 "050501
T05090" 5222860

automatic controlling means.

In the present invention, any actuating means or unit for the cutter tool can be used, and the actuating means includes various reciprocally movable means or mechanism such as an air hydraulic cylinder and the like in addition to the oil hydraulic cylinder. As the actuator for the stopper, various actuating means can also be utilized. The preferred actuating means includes an cylindrical actuating means.

10 In accordance with the shape or configuration of the final product, the cutting site may be selected suitably. The intermediate molded article may be cut at one end or edge (unnecessary portion) or both ends of a hollow molded article.

15 The blade of the cutter unit may have various shapes in accordance with the shape of the intermediate molded article to be cut, and the blade (or tip blade) may be a flat or linear blade, an inclined blade, a crescent or semicircular blade or the like. For improving cutting efficiency, the blade has usually at least an inclined or 20 curved blade which contacts pointedly (or in point) or linearly substantially with the surface of the intermediate molded article at the cutting site.

The metal mold practically accommodates at least 25 side wall of the parison, and the stopper may be preferably displaceable or reciprocal forward or backward against (or along axial direction of) an end of the resin parison and

09873295-060501

closable tightly the end of the resin parison in association or cooperation with movement of the mold members.

The cutting direction by the cutting means is not particularly restricted and may be an oblique direction,
5 a perpendicular direction relative to the axial direction of the molded article to be cut.

The blow-molding apparatus essentially only comprises a pair of metal mold members, a blowing means for blowing a pressurized gas into the resin parison, a
10 cutting means, and a reciprocating means for reciprocating the cutting means. Further, the control unit as a controlling means may comprise a first actuating unit or circuit for actuating a cylinder to advance a cutting means forward from an original position to a given advanced
15 position for cutting a predetermined site of the intermediate molded article, a second actuating unit or circuit for actuating the cylinder backward after completion of the cutting operation, and a reset unit or circuit for resetting the cylinder at the original
20 position.

When the apparatus is provided with the stopper, the control unit may further comprise a unit or circuit for controlling the forward movement or advancement of the stopper relative to the end of the parison in response to
25 the closing operation of the metal mold members, in addition to a unit or circuit for controlling the forward or backward movement of the cutting means in response to the backward

00073295-060501

or forward movement of the stopper. In the operations by the control unit, the stopper may inhibit the cutting operation by a cutting means at the advanced position, and allow to cut the molded article by the cutting means at the backward position.

The closing or opening operation of the metal mold member may be carried out manually by hand or automatically by the control unit, and the blowing operation may be conducted by use of the control unit. Thus, the control unit may further comprise a unit sending a closing signal to an actuating unit for closing the metal mold members in response to the start signal after completion of the setting of the parison in or on the one metal mold member, a unit sending a blowing signal to the blowing unit for blowing a pressurized gas into the parison in the cavity after completion of the closing operation, and a unit sending an opening signal for opening the metal mold members in response to completion of the cutting operation.

The molten resin parison can be various thermoplastic resins such as olefinic resins (e.g. a polyethylene, a polypropylene, an ethylene-propylene copolymer, an ethylene-vinyl acetate copolymer), polyvinyl chloride resins, styrenic resins, (meth)acrylic resins, polyester resins, polycarbonate resins and polyamide resins. The parison may have a single-layer structure or a multi-layer structure.

The present invention can apply to a blow-molding

09873295-060501

process for producing various resin hollow product, and the hollow product may have any two- or three-dimensional configuration such as a linear, a bending or curved shape.

According to the present invention, labor savings
5 can be realized and the generation of defective or non-conforming articles can be inhibited in the cutting operation of the unnecessary section of the final product, and the production efficiency of the hollow product can be improved remarkably with reducing of the production
10 cost.

09073295-060501